



公差/General Tolerances(mm)	
0	>3
~	>6
3	>10
~	>18
6	>30
10	>50
18	>80
30	>120
50	>180
80	>250
120	>315
180	>400
250	>500
315	>630
400	>800
500	>1000
±0.12	±0.18
±0.18	±0.22
±0.26	±0.31
±0.37	±0.57
±0.80	±1.05
±1.05	±1.15
±1.60	±2.20
±2.50	±2.50
±Z	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing 1	PA66	UL94V-0
2	Side Housing	PA66	UL94V-0
3	Cover 1	PA66	UL94V-0
4	Cover 2	PA66	UL94V-0
5	Pin	Copper	Sn Plated
6	Spring	Stainless Steel	
7	Housing 2	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3		
绝缘/Insulation Degree	II/2		
额定电压/电涌/Rated Voltage(V)/Current(A)	/	320/20	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	/	4	/
线芯范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/22~14		
间距/Pitch(mm)/线芯范围/Poles	5.00/N=02~24P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	PANTONE 7534u		

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司

CHKD: /
 DRAFT: CenX 2020.06.15
 DRAWING NO.: BEDGKRMA-5.0-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE