


公差等级/General	Tolerances(mm)										公差/General		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
3	~	~	~	~	~	~	~	~	~	~	~	~	±Z
6	~	~	~	~	~	~	~	~	~	~	~	~	±Z
10	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50



ITEM	NAME OF PART	MATERIAL	NOTES
7	Clapboard	PA66	UL94V-0
6	Pin header	Copper	Sn plated
5	Spring	Stainless steel	
4	Button	PA66	UL94V-0
3	Cover	PA66	UL94V-0
2	Center Housing	PA66	UL94V-0
1	Left Housing	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/12	/	300/10
IEC 标准 /IEC Standard:			
额定电压/电涌 /Rated Voltage(V)/Current(A)	III/3	III/2	II/2
工频耐压 /Withstanding Voltage(V/Min)	/	750/16	/
额定电压/电涌 /Rated Voltage(V)/Current(A)	/	AC3000	/
线芯范围 /Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~2.5/20~12		
间距/Pitch(mm)/线数范围/Poles	10.0/N=02~16P		
引线长度/Stripping length(mm)	10~11		
使用温度范围 /Operating temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD: LIGL	2020.06.03
CHKD: Mek	2020.06.03
DRAFT: LuoXM	2020.06.03
NAME:	DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
DRAWING NO.:	DG202-10.0-C01

REV	ECH	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				
5				
6				

SIZE: A4	mm
TYPE: CUSTOMER DRAWING	
SCALE: 2.5:1	SHEET
REV	T7
1/1	