



精度等级/General Tolerances(mm)												0.1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	±Z	
3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500		
±0.12		±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
5	Current carrier 2	Copper	Sn Plated
4	Current carrier 1	Copper	Sn Plated
3	Spring	Stainless steel	/
2	Button	PA66-GF	UL94V-0
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: LIGL 2020.04.01	NAME: <b>DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD</b>
CHKD: MoEK 2020.04.01	<b>DSKK2.5-01P-1Y-00A(H)</b>
DRT: YonH 2020.04.01	DRAWING NO.: DSKK2.5-C01
	TYPE: CUSTOMER DRAWING
	SCALE: 1:1
	REV: DD-7
	SHEET: 1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/20	300/20	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	500/22	/	/
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	6.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AMG)	0.2~2.5&4(S0L)/26~12		
间距/Pitch(mm)	5.20		
剥线长度/Stripping length(mm)	11~12		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		