



公差/General Tolerances(mm)	
0	>3
3	6
6	10
10	18
18	30
30	50
50	80
80	120
120	180
180	250
250	315
315	400
400	500
500	>500
EZ	

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Button	PA66-GF	UL94V-0
3	Spring	Stainless steel	
4	Current carrier	Copper alloy	Sn Plated
5	Grounding	Copper	Sn Plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:	Li GL 2020.04.03	NAME:	DS1.5-QU-PE-01P-1C-00A(H)
CHKD:	Moo J 2020.04.03	DRAWING NO.:	DS1.5-QU-PE-C01
DRAFT:	MEK 2019.08.27	TYPE:	CUSTOMER DRAWING
SIZE:	A4	SCALE:	2:1
			SHEET 1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/特类等	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/
额定扭矩/Torque Tightening(N.m/Lb.in)	/	/	/
线径范围(裸线/带绝缘)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.14~1.5/ 26~16	1.4(SOL)	
剥线长度/Stripping length(mm)	3.5		
使用温度范围/Operating Temperature(°C)	8~10		
符合RoHS要求/Conform to RoHS	-40~+105		
标准颜色编号/Standard color number:	Yes		
PANTONE / RAL	/		

DEGSO<sup>®</sup> NINGBO DEGSO ELECTRICAL CO., LTD  
 宁波高松电子有限公司