



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>6	>18
~	~	~	~
3	6	10	18
~	~	~	~
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±2.50	±2.50	±2.50
0.1/10	0.1/10	0.1/10	0.1/10
±2	±2	±2	±2

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:			
CHKD:			
DRAFT:	WU NK 2020.5.26	DRAWING NO.:	DG55S-C03
		TYPE:	CUSTOMER DRAWING
		SCALE:	1:1
		SHEET	1/1

NAME:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
DRAWING NO.:	DG55S-C03	REV	T0

3	Screw	Steel	Ni Plated
2	Pin header	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:		B	C
			D
额定电压/电流/Rated Voltage(V)/Current(A)	300/20	300/20	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	600/32	600/32	1000/32
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	6	6
额定扭矩/Torque Tightening(N·m/Lb·in)	M4, 1.2/10.53		
线径范围(导线)/Wire Range(flexible)(AWG)	22~12		
间距/Pitch(mm)/线数范围/Poles	10.00/N=02~24P		
剥线长度/Stripping length(mm)	9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

C

B

A

D

1

2

3

4

5

6

REV	ECN	DESCRIPTION	DRAFT	DATE

SIZE:	A4	UNIT:	mm
TYPE:	CUSTOMER DRAWING	SCALE:	1:1
SHEET	1/1	REV	T0