


标注公差 (General tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.7	±2



ITEM	NAME OF PART	MATERIAL	NOTES
7	Housing 2	PA66	UL94V-0
6	Spring	Stainless Steel	
5	Pin	Copper	Sn plated
4	Cover 2	PA66	UL94V-0
3	Cover 1	PA66	UL94V-0
2	Side housing	PA66	UL94V-0
1	Housing 1	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准 /IEC Standard:			
过压类别 /Overvoltage Category/ 污染等	III/3	III/2	II/2
绝缘 /Pollution Degree	/	320/20	/
额定电压/电涌 /Rated Voltage(V)/Current(A)	/	/	4
额定脉冲电压 /Rate Impulse Voltage(KV)	0.2~2.5/22~14		
线芯范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG)	5.08/N=02~24P		
间距 /Pitch(mm) /线芯范围 /Poles	9-10		
剥线长度 /Stripping length(mm)	-40~+105		
使用温度范围 /Operating temperature(°C)	Yes		
符合RoHS环保要求 /Conform to RoHS			
标准颜色编号 /Standard color number:	PANTONE 7534u		

MATERIAL:	/	SURFACE:	/
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/		
APPD:		NAME:	8EDGKRMB-5.08-XXP-11-01A(H)
CHKD:		DRAWING NO.:	8EDGKRMB-5.08-C02

REV	ECN	DESCRIPTION	DRAFT	DATE	SCALE	SHEET
(1)	18-0139	Change drawing	CZ	2018.05.24	SCALE: 2:1	1/1