



公差表/General tolerances(mm)		公差表/General tolerances(mm)	
0	>3	>10	>180
~	>6	>30	>315
~	>10	>120	>400
3	~	~	>500
6	10	50	80
~	18	~	120
~	30	~	180
~	50	~	250
~	80	~	315
~	120	~	400
~	180	~	500
~	250	~	~
~	315	~	~
~	400	~	~
~	500	~	~
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±0.93	±1.05	±1.15	±1.60
±2.20	±2.50	±2.50	±2.50

4	Pin header	Copper alloy	M2/Sn plated
3	Screw	Steel	M2/Zn plated
2	Spring	Stainless steel	/
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/7	/	300/7
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等	III/3	III/2	II/2
级/ Pollution Degree			
额定电压/电流/Rated Voltage(V)/Current(A)	/	130/10	/
工频耐压/Withstanding voltage(V/1Min)	AC1250		
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M2: 0.20/1.77		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.5~1.0/24~18		
间距/Pitch(mm)/线数范围/Poles	3.96/N=02~24P		
剥线长度/Stripping length(mm)	5		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL:

SURFACE:

MAT NO.: /
 STATUS: /
DEGSON 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

APPD:lan CHH 2020.05.25
 CHKD:Yu JZh 2020.05.25
 DRT: Song 2016.01.20
DEGSON 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD
 NAME: **DG350R-3.96-XXP-1Y-00A(H)**
 DRAWING NO.: DG350R-3.96-C04

REV	ECN	DESCRIPTION	DRT	DATE	SIZE: A4	SCALE: 4:1	SHEET
1					mm		1/1
2					mm		1/1
3					mm		1/1
4					mm		1/1
5					mm		1/1
6					mm		1/1