






0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50		



4	Pin header	Copper alloy	M2.5/Sn Plated
3	Spring	Stainless steel	
2	Screw	Steel	M2.5/Zn Plated
1	Housing	PBT	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	/	P50/17.5	/
工频耐压/Withstanding voltage(V/1min)	AC2000		
拧紧扭矩/Torque Tightening(N·m/Lbin)	M2.5: 0.4/3.5/4		
线材范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/22~14		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~22P		
剥线长度/Stripping length(mm)	5~6		
使用温度范围/Operating temperature(°C)	-30~+120		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:
 MAT NO.: /
 STATUS: /
 APPD: Lon CHH 2020.05.25
 CHKD: Yu JZh 2020.05.25
 DRT: Hooyh 2006.03.20
 DRAWING NO.: DG301R-C02
 TYPE: CUSTOMER DRAWING
 SCALE: 4:1
 SHEET 1/1

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
宁波高松电子有限公司
 DG301R-5.0-XXP-1Y-00A(H)

REV	ECN	DESCRIPTION	DRT	DATE	SIZE: A4	SCALE: 4:1	REV	T1

1 2 3 4 5 6