



mm	Pitch range in		Nominal dimension range	
	Over	Under	Over	Under
6	10	6	30	01/10
10	10	10	60	150
24	10	10	100	150
30	60	100	±1.00	±1.30
±0.15	±0.20	±0.30	±0.30	±1.00

2	Pin	Copper	Sn Plated
1	Housing	PA66	UL94 V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 / UL Standard:	B	C	D
额定电压/电涌 / Rated Voltage(V)/Current(A)	300/15	150/15	300/10
IEC 标准 / IEC Standard:	III/3	III/2	II/3
过压类别 / Overvoltage Category / 污染等	III/3	III/2	II/3
绝缘 / Pollution Degree	3	2	3
额定电压/电涌 / Rated Voltage(V)/Current(A)	320/20	/	/
额定电涌电压(KV) / Rate Impulse Voltage(KV)	4	/	/
间距 / Pitch(mm) / 线数插脚 / Poles	5.0	N=02~12P	
使用温度范围 / Operating Temperature(°C)	-40~+105		
符合RoHS标准要求 / Conform to RoHS	Yes		

MATERIAL: /

MAT NO.: /

STATUS: Valid

APPD: /

CHKD: /

DRT: WJW 2017.04.05

NAME: **DEGSON** NINGBO DEGSON ELECTRICAL CO., LTD
8EDGRCB-7.5-XXP-11-01A(H)

DRAWING NO.: 8EDGRCB-7.5-C01

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				
5				
6				



SIZE: A4

mm / inch

TYPE: CUSTOMER DRAWING SCALE: 2:1 SHEET 1/1