



		尺寸公差(mm)			
		0	>30	>60	>100
Rated current	16A	~	~	~	0.05/10
Rated voltage	300V	30	60	100	±T
Coil/Contact dielectric voltage	4000V/S	~	~	~	>150
Dielectric voltage between contact	2500V/S	±0.20	±0.30	±0.50	±0.70 ±1.00
Screw torque	1.0Nm				
External connection wire	20-14/0.5-2.5W				
Ambient temperature	5/1mm ²				
Key controlled symbol	-45~+85°C				*
Conform to RoHS					

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

REV ECN

DESCRIPTION

DRAFT DATE

SIZE: A4

TYPE: PRODUCT DRAWING

SCALE: 1:1

DRAWING NO.: 30000365

REV TO-1

SHEET 1/1

REV TO-1

SHEET 1/1

NO.	DESCRIPTION	MATERIAL NO.	QTY	MATERIAL	NOTES
1	DSRT05A-3-00A(H)-N	30019000038	1		

MATERIAL: / SURFACE: /

MAT. NO.: 30020000057

STATUS: /

APPD: /

CHKD: /

DRAFT: /

NINGBO DEGSON ELECTRICAL CO., LTD

DSRT05A-3-00A(H)

1

2

3

4

5

6

D

C

B

A