



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>6	>18
~3	~6	~10	~30
~6	~10	~18	~50
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±2.50	±2.50	±2.50
±2	±2	±2	±2



3	Screw	Steel	M3 N Plated
2	Pin Header	Brass	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard: B C D			
额定电压/电流/Rated Voltage(V)/Current(A): 300/15 / 300/10			
IEC 标准/IEC Standard: /			
过压类别/Overvoltage Category/污染等级/ Pollution Degree: III/3 III/2 II/2			
额定电压/电流/Rated Voltage(V)/Current(A): 300/24 300/24 600/24			
额定脉冲电压/Rate Impulse Voltage(KV): 4 4 4			
额定电压/电流/Rated Voltage(V)/Current(A): M3, 0.5/4, 4.3			
扭矩/Torque Tightening(N·m/Lb·in): 0.34~2.5/22~14			
导线范围/Wire Range(frigid and flexible)(mm²/AWG): 7.62/N=02~24P			
间距/Pitch(mm)/导线范围/Poles: /			
剥线长度/Stripping length(mm): -40~+105			
使用温度范围/Operating temperature(°C): Yes			
符合RoHS环保要求/Conform to RoHS: Yes			

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: /

CHKD: /

NAME: **DEGSON** 宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: DG25H-E04  
TYPE: CUSTOMER DRAWING  
SCALE: 1:1  
REV: T0  
SHEET: 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE