



未注公差/General tolerances (mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10 ±2'
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~500		
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
UL 标准/UL Standard:											B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)											300/20	300/20	300/10
IEC 标准/IEC Standard:													
过压类别/Overvoltage Category/污染等级/Pollution Degree											III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)											500/22	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)											6	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)											0.2~2.5&4(sol) /26~12		
线数范围/Poles											N=01P		
剥线长度/Stripping length(mm)											11~12		
使用温度范围/Operating temperature(°C)											-40~+105		
符合RoHS环保要求/Conform to RoHS											Yes		

5	Current carrier 2	Copper	Sn Plated
4	Current carrier 1	Copper	Sn Plated
3	Spring	Stainless steel	/
2	Button	PA66+GF%	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

			MATERIAL: /		SURFACE/COLOR: /		
			MAT NO./REV: /		MAT STATUS: /		
APPD:	Li GL	2022.06.14	NAME				
CHKD:	Ma EK	2022.06.14	DSKK2.5-01P-1Y-00A(H)				
DRFT:	Zheng QG	2022.06.14	DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
			/	CUSTOMER DRAWING	/	1:1	1/1

00	/	/	Zheng QG	2022.06.14
REV	ECN	DESCRIPTION	DRFT	DATE

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in advance. All rights reserved for patent. 除专利注明限制外，其他部分均受版权保护。未经授权，不得复制或传播本文件中的任何内容。本公司保留对涉及发明、实用新型和外观设计的所有权利。