




01P



02P



03P



04P

未注公差/General tolerances(mm)												0.1/10	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315		>400
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

Note: The A&Z(H) in the name means: A(H) and Z(H).

ITEM	NAME OF PART	MATERIAL	NOTES
10	Cage2	Copper alloy	Ni Plated
9	Spring2	Stainless Steel	/
8	Screw	Steel	M3/Zn Plated
7	Clamp	Copper alloy	Ni Plated
6	Spring1	Stainless Steel	/
5	Cage1	Copper alloy	Ni Plated
4	Current Carrier	Steel+Copper alloy	Ni Plated
3	Housing3	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)(DG801F)	300V/6.3	/	300/10
UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)(DG801H)	600V/15	/	600/5
IEC 标准/IEC Standard(DG801F):			
额定电压/电压/Rated Voltage(V)/Current(A)	/	250/6.3	/
IEC 标准/IEC Standard(DG801H):			
额定电压/电压/Rated Voltage(V)/Current(A)	/	450/24	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm ²)	22~14/ 0.5~2.5		
间距/Pitch(mm)/线数范围/Poles	10.00/N=01~05P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		

		MATERIAL:	SURFACE/COLOR:		
APPD: 蓝贵凡 2022.11.11		MAT NO./REV: - / 00	MAT STATUS: 批量		
CHKD: 曹利彬 2022.11.09		NAME			
DRFT: 姜民洁 2022.11.09		DG801-XXP-1Y-00A&Z(H)			
DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET	
200043121	CUSTOMER DRAWING	已发布	1:1	1/1	

REV	ECN	DESCRIPTION	DRFT	DATE
00		由T2转成5P格式00版本	姜民洁	2022.11.09

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized. All rights reserved for patent, utility model or design registrations. 非经明确授权, 否则禁止转让、复制、利用、交加本文件的内容, 一经发现负法律责任, 侵权者将依法追究。 未经授权, 不得复制或传播。 非经明确授权, 否则禁止转让、复制、利用、交加本文件的内容, 一经发现负法律责任, 侵权者将依法追究。