

Aperçu

informations sur le produit



Bus IO-DF750-002-11-2001A(H)-30050000130

Card type IO shell, can be equipped with RJ45 connector, LED indicator

Les avantages des produits

- ☑ Dual network port with light RJ45 interface
- ☑ 8-bit address interface
- ☑ Internal bus through 6 gold-plated terminals at the bottom
- ☑ Equipped with 8 channels power module, each node is equipped with LED
- ☑ Two internal gold-plated blade connectors are used for power cascade expansion
- ☑ Can be installed on DIN rail

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
---------------------------------	-----------

Ambient temperature (storage / transport)

-40℃～+70℃

Connection method(IO)

wiring

Spring type wiring technology

Strip length

8-9mm

Power contacts

2 blade contacts

Power load

10A

Rated current

Power: 24V Bus connector: 5V

Cross section

0.2~2.5mm²

Connectable guide cross section AWG

28~12AWG

PCB thickness

1.0mm

Dimension

length

93.5mm

width

48mm

Height

69mm

Accessoires

Accessories

IO housing

DF750-200-11-2001A(H)

Caractéristiques commerciales

Numéro de la commande

30050000130

Unité d'emballage

20

Quantité minimale de commande

20

Le poids de produit (sans emballage)

122.5

