

Aperçu

informations sur le produit



Interface module-DT010-00A(H)-30040000095

16 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 16 positionsNPN/PNP signal,can be installed on DIN35 rail

Les avantages des produits

Suitable for 16-point (20-bit interface) controller, Screw connection

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
-----------------------	-----------

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	16
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	20
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	65.5mm
width	57mm
Height	43mm

Accessoires	
Accessories	
Wire harness	DX213-1S-500-00A(H)

Caractéristiques commerciales	
Numéro de la commande	30040000095
Unité d'emballage	1
Quantité minimale de commande	10
Le poid de produit (sans emballage)	87