

Aperçu

informations sur le produit



Interface module-DT007-00A(H)-30040000094

32 positions input output module,with indicator light,with screw connector and IDC stitching line,can access 32 positions NPN signal,can be installed on DIN35 rail

Les avantages des produits

Suitable for 32-point (34/40-bit interface) controller, Screw connection

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location

Arbitrary

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	32
Status Display	Yes

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	34
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	111mm
width	57mm
Height	47mm

Accessoires	
Accessories	
Wire harness	DX210-4S-500-00A(H)

Caractéristiques commerciales	
Numéro de la commande	30040000094
Unité d'emballage	1
Quantité minimale de commande	10
Le poid de produit (sans emballage)	128