

Aperçu

informations sur le produit



Interface module DM50-IDC-10-10-4G-00A(H)-30040000055

IDC module, japanese terminal block, with screw connector and IDC stitching line, can be installed on DIN35 rail, 10 positions

Les avantages des produits

10digits to 50digits
1:1 connection
Screw connection

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	10
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	0.3mm ² --2.0mm ²
Connectable guide cross section AWG	22-14AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3
Hard wire cross section	0.3mm ² --2.0mm ²

Dimension

length	66mm
width	57mm

Height	44mm
--------	------

Accessoires

Accessories

Wire harness	DX211-1S-500-00A(H)
--------------	---------------------

Caractéristiques commerciales

Numéro de la commande	30040000055
Unité d'emballage	6
Quantité minimale de commande	12
Le poid de produit (sans emballage)	70