

Aperçu

informations sur le produit



Relay module-DM72-RMUS-08-PN-1-44-01A(H)-30030000034

Subminiature Relay Module, with relay Socket, 16 relays can be installed, with relay Socket, with indicator light, Honfa relay, PNP or NPN signal can be input

Les avantages des produits

- ☒ Each signal channel and power supply voltage have LED status indicators
- ☒ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
- ☒ Suitable for NPN, PNP controller
- ☒ Freewheeling diode for each signal path

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-20 °C ... 70 °C
---	------------------

Standards/Regulations

Standards/Regulations	IEC61810
-----------------------	----------

Pollution level	3
-----------------	---

Overvoltage category	III
----------------------	-----

Dimension

length	60mm
--------	------

width	90mm
-------	------

Height	60mm
--------	------

Overview

Installation location	Arbitrary
Number of channels	8
Shell Insulation Materials	PVC/PA66
color	green

Accessoires

Caractéristiques commerciales

Numéro de la commande	30030000034
Unité d'emballage	4
Quantité minimale de commande	4
Le poid de produit (sans emballage)	128