

Aperçu

informations sur le produit



40A-GF-2.5-92116000494

40A silver gold female pins, Adapter wire specification 2.5mm²

Les avantages des produits

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	2.5mm²
Conductor cross sections(AWG)	14AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9mm
working life-mating cycles	≥500

Accessoires

Caractéristiques commerciales

Numéro de la commande	92116000494
Unité d'emballage	100
Quantité minimale de commande	100
Le poid de produit (sans emballage)	2.701