

Aperçu

informations sur le produit



5A-GM-0.25-92116900066

5A silver gold male pins, Adapter wire specification 0.25mm²

Les avantages des produits

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D



Marking

classification	Contact
Series	5A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	0.25mm²
Conductor cross sections(AWG)	24AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	8mm
working life-mating cycles	≥500

Accessoires

Caractéristiques commerciales

Numéro de la commande	92116900066
Unité d'emballage	100
Quantité minimale de commande	100
Le poid de produit (sans emballage)	0.186