

Aperçu

informations sur le produit

**D24B-SF-4g-CV-2M25-21010000356**

24B Lower base, Four levers, back cover, side entry, double M25 Thread hole, Wear protective cover

Les avantages des produits

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D



Marking

classification	Upper Housing/base
Series	B
Type	Surface mount base
Description	With plastic dust cover
Specification	Low structure

versions

Dimension	24B
locking Category	Double lock
Thread specification	2x M25

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR

Technical specification

Limiting temperatures	-40°C~+125°C
IP class	IP65

Accessoires

Caractéristiques commerciales

Numéro de la commande	21010000356
Unité d'emballage	100
Quantité minimale de commande	1
Le poid de produit (sans emballage)	305