

Aperçu

informations sur le produit



D6B-SF-1L-2PG13.5-21010000438

6B Lower base,single buckle,back cover ,side entry,double PG13.5 Thread hole

Les avantages des produits

- ☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑Snap-in combination structure, dustproof, waterproof, easy operation;

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Marking

classification	Upper Housing/base
Series	B
Type	Surface mount base
Specification	Low structure

versions

Dimension	6B
locking Category	Single lock
Thread specification	2x PG13.5

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40℃~+125℃
IP class	IP65

Accessoires

Caractéristiques commerciales

Numéro de la commande	21010000438
Unité d'emballage	100
Quantité minimale de commande	1
Le poid de produit (sans emballage)	189