


Aperçu

informations sur le produit



DA-016-M-21020000008

Heavy-duty insert, Number of contacts: 16+PE, Dimension: 16A, Rated voltage :250V, Rated current: 16A, Male insert, Screw connector

Les avantages des produits

- ☑ Screw connection technology, applicable to a wide range of wire specifications;
- ☑ No need special tools, easy to operate;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection.

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Marking

classification	Insert
Series	DA

versions

Connection method	Screw connection
Female/Male	Male
Dimension	16A
Number of positions	16
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Rated torque	0.5N.m
Conductor cross sections (mm²)	0.75-2.5mm²
Conductor cross sections(AWG)	18-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessoires

Accessories

Screwdriver

/

Caractéristiques commerciales

Numéro de la commande	21020000008
Unité d'emballage	100
Quantité minimale de commande	5
Le poid de produit (sans emballage)	64.56