


Aperçu

informations sur le produit



PC2.5-11010000031

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 2.5 mm², AWG: 24 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Les avantages des produits

- ☒ Screw connection technology, reliable connection;
- ☒ Equipped with fixed parts and bridge parts, circuit connection test is more flexible;
- ☒ Copper alloy material, good corrosion resistance;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-0.75mm ²
Strip length	8~9mm
Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	24~12
screw thread	M3
Tightening torque	0.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	24A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	47.25mm
End plate width	1.6mm
NS 35/15 Height	54.75mm
length	42.5mm
width	5.2mm
Height	46mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Fixed bridge	FBRIXX-5
Insertion bridge	EB2-5 / EB3-5 / EB10-5
End cover	D-PC2.5
Separating disk	TS-K
Partition plate	ATP-PC

Marker

Top marker	/
Marker	ZB5
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB5
Marker cards	DBE-1

Accessories

End cover	D-PC2.5
Grouping Partition plate	TS-K
Partition plate	ATP-PC
Bridge	FBRIXX-5
End clamp	E-WS

DIN rail

NS35/7.5-1000-00A(H)

Caractéristiques commerciales

Numéro de la commande	11010000031
Unité d'emballage	50
Quantité minimale de commande	50
Le poids de produit (sans emballage)	7.233