

Aperçu

informations sur le produit



PC1.5-11010000017

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 500 V, Rated current: 17.5 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 1.5 mm², AWG: 26 - 16, Width: 4.2 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Les avantages des produits

- ☒ Screw connection technology, reliable connection;
- ☒ Equipped with fixed parts and bridge parts, circuit connection test is more flexible;
- ☒ Copper alloy material, good corrosion resistance;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Wiring data

Screw type	Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.2-0.5mm ²
Strip length	6~7mm
Conductor cross section solid	0.2~1.5mm ²
Conductor cross section flexible	0.2~1.5mm ²
Conductor cross section solid AWG	26~16
screw thread	M2

Tightening torque	0.2N.m
-------------------	--------

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	17.5A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	42.05mm
End plate width	1.5mm
NS 35/15 Height	49.55mm
length	42.5mm
width	4.2mm
Height	40.8mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.4×2.5
Fixed bridge	FBRIXX-4
Insertion bridge	/
End cover	D-PC1.5
Separating disk	/
Partition plate	ATP-PC

Marker

Top marker	/
Marker	ZB4
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB4
Marker cards	DBE-1

Accessories

End cover	D-PC1.5
Partition plate	ATP-PC
Bridge	FBRIXX-4
End clamp	E-WS

DIN rail

NS35/7.5-1000-00A(H)

Caractéristiques commerciales

Numéro de la commande	11010000017
Unité d'emballage	100
Quantité minimale de commande	100
Le poids de produit (sans emballage)	4.22