

Aperçu

Informations sur le produit



SP-M12D-04P-MM-SH8001-20030001290

Sensor/Actuator Female socket, M12, Coding D, Unshielded, Front panel installation/PG9 Thread mounted, 180° vertical pins

Les avantages des produits

- ☒ Sealing optimization, protection level up to IP68
- ☒ Meet the harsh environment
- ☒ Suitable for various occasions connection technology
- ☒ Compatible with the international and domestic same series products

Les certificats des produits



RoHS

REACH



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP68

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Accessoires

Accessories

Sealing cap	CAP-M12-FP-8002
-------------	-----------------

Caractéristiques commerciales

Numéro de la commande	20030001290
Unité d'emballage	/
Quantité minimale de commande	100

Le poid de produit (sans emballage)	/
-------------------------------------	---