

Aperçu

informations sur le produit



PB-M12A-04P-MM-SL7001-20030000026

Field mounted, Male, Straight, M12, Coding A, Screw connector, Cable External cable diameter 4.0~8.0 mm

Les avantages des produits

- ☑ Sealing optimization, protection level up to IP67
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

Les certificats des produits

RoHS REACH

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

Overvoltage level	II
Pollution level	3
Connection method	Screw connection
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Dimension

Assembled cable outer diameter	4.0-8.0mm
Assembled conductor cross section	0.25~0.52 mm²
	24~20 AWG

Accessoires

Accessories

Sealing cap	CAP-M12-FP-8004
-------------	-----------------

Caractéristiques commerciales

Numéro de la commande	20030000026
-----------------------	-------------

Unité d'emballage	/
Quantité minimale de commande	100
Le poid de produit (sans emballage)	/