

Aperçu

informations sur le produit



PM-M12T-04P-FF-SR8B01-20030000850

Sensor/Actuator Cable,PUR,black,UL20549,Female plug,acodado M12,Coding T,Unshielded,Trimming cable end,Cable Cable length:1m

Les avantages des produits

- ☑ Sealing optimization, protection level up to IP68
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

Les certificats des produits

RoHS REACH

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Environmental conditions

Ambient temperature	-25°C...80°C
---------------------	--------------

IP class	IP68
----------	------

General parameters

Rated current	12A
---------------	-----

63V

Number of potentials	4
----------------------	---

Insulation resistance	≥ 100 MΩ
-----------------------	----------

Error-proof coding	T-Code
--------------------	--------

Overvoltage level	III
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-111
--------------------------	-----------------

Cable

Cable type	PUR Black
Cable type(abbreviation)	PUR
UL AWM form	UL20549
Cross section	1.31mm ²
AWG signal wire	16AWG
Wire structure Signal wire	26/0.254mm ²
Core diameter (including insulation layer)	2.3±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black
Thickness, insulation	0.68mm
Cable outer diameter D	7.8mm
Minimum bend radius ,fixed installation	5*OD

Minimum bend radius ,mobile installation	10*OD
Bending times	4 million times
Bending radius	50.8mm
Cable weight	105.5kg/km
Outer sheath, material	PU
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	10MΩ
Conductor resistance	Maximum 14.6Ω/km (at 20 °C))
Nominal cable voltage	300V
Cable test voltage	2000V
Special attributes	Silicone-free
Flame retardant	VW-1
Other protection functions	Anti-UV

Dimension

Cable length	1m
--------------	----

Accessoires

Accessories

Sealing cap	CAP-M12-MP-8001
-------------	-----------------

Caractéristiques commerciales

Numéro de la commande	20030000850
Unité d'emballage	/
Quantité minimale de commande	100

Le poids de produit (sans emballage)	/
--------------------------------------	---