

## Aperçu

### Informations sur le produit



**PM-M12A-05P-FF-SL8C01-20030000677**

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,Straight M12,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m,UL Certification

### Les avantages des produits

- ☑ Sealing optimization, protection level up to IP68
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

### Les certificats des produits



**RoHS**

**REACH**



## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

□

### Environmental conditions

Ambient temperature

-25°C...85°C

IP class

IP68

### General parameters

Rated current

4A

60V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

|                             |        |
|-----------------------------|--------|
| Overvoltage level           | II     |
| Pollution level             | 3      |
| Insertion and pullout cycle | ≥ 100  |
| Torque                      | 0.4 Nm |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL94 | V0                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PA                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

Standards and specifications

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |
|--------------------------|-----------------|

Cable

|                                            |                                       |
|--------------------------------------------|---------------------------------------|
| Cable type                                 | PVC Black                             |
| Cable type(abbreviation)                   | PVC                                   |
| UL AWM form                                | UL2517                                |
| Cross section                              | 0.34mm <sup>2</sup>                   |
| AWG signal wire                            | 22AWG                                 |
| Wire structure Signal wire                 | 17/0.16mm <sup>2</sup>                |
| Core diameter (including insulation layer) | 1.30±0.05mm                           |
| Wire color                                 | 1 Brown 2 White 3 Blue 4 Black 5 Gray |
| Thickness, insulation                      | 0.6mm                                 |
| Cable outer diameter D                     | 5.4 ±0.2mm                            |

|                               |                                                                   |
|-------------------------------|-------------------------------------------------------------------|
| Outer sheath, material        | PVC                                                               |
| Conductor insulation material | PVC                                                               |
| Conductor material            | Tinned copper                                                     |
| Insulation resistance         | $\geq 100\text{M}\Omega$                                          |
| Conductor resistance          | Maximum $59.4\Omega/\text{km}$ (at $20\text{ }^{\circ}\text{C}$ ) |
| Nominal cable voltage         | 300V                                                              |
| Cable test voltage            | 2000V                                                             |
| Flame retardant               | Comply with UL 758/1581 FT1 standard                              |
| Halogen free                  | Yes                                                               |

#### Dimension

|              |    |
|--------------|----|
| Cable length | 1m |
|--------------|----|

#### Accessoires

##### Accessories

|             |                 |
|-------------|-----------------|
| Sealing cap | CAP-M12-MP-8001 |
|-------------|-----------------|

#### Caractéristiques commerciales

|                                      |             |
|--------------------------------------|-------------|
| Numéro de la commande                | 20030000677 |
| Unité d'emballage                    | /           |
| Quantité minimale de commande        | 100         |
| Le poids de produit (sans emballage) | /           |