

Aperçu

informations sur le produit

**DG89-A-12050000052**

Transfer barrier terminal blocks, Rated current: 30A. Rated voltage (UL) : 300V, Cross section: 22~10AWG, pitch: 14.00mm, Color: black, Contact surface: Tin

Les avantages des produits

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Panel mounting for electrical transfer between two devices in a small space

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D



Connection capacity

AWG	22~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	30A
Rated current (D)	5A

Rated current (C)	30A
-------------------	-----

Electrical parameters IEC

Rated current	1000V
	41A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	14mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

Accessoires

Accessories

Caractéristiques commerciales	
Numéro de la commande	12050000052
Unité d'emballage	180
Quantité minimale de commande	/
Le poid de produit (sans emballage)	25.1