

Aperçu

informations sur le produit

**TSF2.5-10070000095**

Transformer terminal blocks, Rated current: 6.3A. Rated voltage
(III/2) : 250V, Color: Orange, Contact surface : Tin

Les avantages des produits

- ✓ Screw connection technology, safe and reliable
- ✓ Rail installation method, suitable for transformer wiring

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Connection capacity

Conductor cross section solid	0.5~2.5mm ²
Conductor cross section flexible	0.5~2.5mm ²
AWG	20~14AWG
Torque	0.8N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	250V
Rated voltage (C)	250V
Rated voltage (D)	250V

Rated current (B)	6.3A
Rated current (D)	10A
Rated current (C)	6.3A

Electrical parameters IEC

Rated current	250V
	6.3A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessoires

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Caractéristiques commerciales

Numéro de la commande	10070000095
Unité d'emballage	250
Quantité minimale de commande	30
Le poid de produit (sans emballage)	9