

Aperçu

informations sur le produit



DGH95-10090000015

Through-wall terminal blocks, Rated current: 232A. Rated voltage (III/3) : 1000V, Width: 25.0mm, Color: gray, Contact surface : Tin

Les avantages des produits

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Connection capacity

Conductor cross section solid	25~95mm ²
Conductor cross section flexible	25~95mm ²
AWG	4~4/0AWG
Strip length	27mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	230A
Rated current (D)	5A

Rated current (C)	230A
-------------------	------

Electrical parameters IEC

Rated current(III/3)	1000V
Rated current	1000V
	232A
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Hexagon screwdriver
screw thread	M8
Pitch	25mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessoires

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Caractéristiques commerciales

Numéro de la commande	10090000015
Unité d'emballage	10
Quantité minimale de commande	30
Le poid de produit (sans emballage)	293