


Aperçu

informations sur le produit



DGH4-10090000008

Through-wall terminal blocks, Rated current: 41A. Rated voltage
(III/2) : 400V, Width: 8.1mm, Color: gray, Contact surface : Tin

Les avantages des produits

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Connection capacity

Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~6.0mm ²
AWG	30~10AWG
Torque	0.5N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V

Rated current (B)	30A
Rated current (D)	10A
Rated current (C)	30A

Electrical parameters IEC

Rated current	400V
	41A
Rated current(III/2)	400V
Rated surge voltage(III/2)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	8.1mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessoires	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Caractéristiques commerciales	
Numéro de la commande	10090000008
Unité d'emballage	50
Quantité minimale de commande	30
Le poid de produit (sans emballage)	10.5