

Aperçu

Informations sur le produit



DG636S-9.52-10040000768

PCB terminal blocks, Rated current: 32A, Rated voltage (III/2) 1000V, Cross section: 0.2~4.0mm², pitch: 9.52mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

Les avantages des produits

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D



Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~6mm²

Conductor cross section flexible

0.2~4.0mm²

AWG

30~10AWG

Torque

0.8N.m

Strip length

9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	30A
Rated current (D)	5A
Rated current (C)	30A

Electrical parameters IEC

Rated voltage	1000V
Rated current(III/3)	690V
Rated current	32A
Rated current(III/2)	1000V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	9.52mm
Number of potentials	2
Pluggable or not	no

Number of rows	1
----------------	---

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessoires

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

Caractéristiques commerciales

Numéro de la commande	10040000768
-----------------------	-------------

Unité d'emballage	465
Quantité minimale de commande	30
Le poid de produit (sans emballage)	8.6