


Aperçu

informations sur le produit



5EDGRM-10.16-10020000948

Pluggable terminal blocks, Rated current: 57A. Rated voltage
(III/3) : 600V, pitch: 10.16mm, Color: green, Contact surface : silver

Les avantages des produits

- ✓ Universal installation method to ensure a high degree of flexibility in device design
- ✓ The plug direction is parallel to the PCB

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	52A
Rated current (D)	5A
Rated current (C)	52A

Electrical parameters IEC

Rated voltage	600V
Rated current(III/3)	600V
Rated current	57A
Rated surge voltage(III/3)	6KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Three rows in a straight line
Pitch	10.16mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	Silver plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	5EDG-PWI

Caractéristiques commerciales	
Numéro de la commande	10020000948
Unité d'emballage	175
Quantité minimale de commande	30
Le poid de produit (sans emballage)	13.521