

## Aperçu

## informations sur le produit

**DSW-A5K0005-30090000001**

5 10/100Mbps BaseT port, IP30, Operating temperature -40°C~+75°C. 12/24/48 VDC & 24VAC (9.6~60 VDC & 18~30 VAC) power supply enter (Only connect to class 2 power).

## Les avantages des produits

- ☒ Unmanaged Industrial Switch made from Anti-Corrosion Aluminum Alloy.
- ☒ 5 10/100BaseT Ports.
- ☒ 12/24/48 VDC & 24VAC (9.6~60VDC & 18~30 VAC) Power Input
- ☒ Operating Temperature from -40°C to +75°C.
- ☒ IP30 Protection Class

## Les certificats des produits

## Caractéristiques techniques

## Dessin de produit

## Modèle 3D

☐

## interface

|                   |             |
|-------------------|-------------|
| Port 1 Type       | RJ45        |
| Number of ports 1 | 5           |
| Transmission rate | 10/100 Mbps |

## Mechanical structure

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| Shell material      | Die-cast aluminum alloy housing                         |
| switch              | QoS function, BSP (Broadcast Storm Protection) function |
| Installation method | Card rail installation                                  |
| Protection class    | IP30                                                    |

## exchange property

|                     |        |
|---------------------|--------|
| MAC table size      | 4K     |
| Bandwidth backplane | 16Gbps |
| packet buffer       | 1.5Mb  |

#### MTBF

|                     |                  |
|---------------------|------------------|
| Standards compliant | Telcordia SR-332 |
| operating hours     | ≥38,7641H        |

#### Warranty

|          |         |
|----------|---------|
| Warranty | 5 years |
|----------|---------|

#### power supply

|                            |                       |
|----------------------------|-----------------------|
| Supply voltage range       | 9.6~60VDC & 18~30VAC  |
| reverse voltage protection | support               |
| Connection Type            | 2P plug-in terminal   |
| connecting wire diameter   | 0.5~1.5mm/ 28~16AWG   |
| Overcurrent protection     | support               |
| Input voltage              | 12/24/48 VDC & 24 VAC |

#### Environmental data

|                       |                           |
|-----------------------|---------------------------|
| working altitude      | ≤2000m                    |
| Operating temperature | -40°C~+75°C               |
| storage temperature   | -40°C~+85°C               |
| humidity              | 5% ~ 95% (non-condensing) |

#### Dimension

|        |        |
|--------|--------|
| high   | 100mm  |
| length | 61.8mm |
| width  | 24mm   |

Accessoires

| Caractéristiques commerciales       |             |
|-------------------------------------|-------------|
| Numéro de la commande               | 30090000001 |
| Unité d'emballage                   | 1 STK       |
| Quantité minimale de commande       | 1 STK       |
| Le poid de produit (sans emballage) | 170g        |