

Aperçu

informations sur le produit



SA-EBBH-2006-F-00A(H)-25080000002

Charging and discharging receptacle at the end of electric motorcycle battery, with rated current of 100A~120A; Rated voltage 72V DC; Withstand voltage 1500V AC; Insulation resistance > 500M Ω ; Protection grade: IP67 when mated &single.Mechanical life $\geq$ 3000 cycles; Pull out force > 20N; Working temperature: - 40 ~ 105 $^{\circ}$ C; Salt spray resistance for 72h; Flame retardant grade ul94-v0; Environmental protection:RoHS

Les avantages des produits

- ☒ Compact structure and high space utilization
- ☒ Adopt bayonet locking structure to prevent accidental unlocking
- ☒ Direct plug operation, convenient and fast
- ☒ Signal pin No.: 0~8 pins
- ☒ Multiple auditory and visual feedback are inserted in place
- ☒ Beautiful appearance, fit human functional design

Les certificats des produits

RoHS

Caractéristiques techniques

Dessin de produit

Modèle 3D

☐

Marking

Series	DA
	DD
	DM

versions

Connection method	Crimping connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	15
	25
	42

Paramètre technique

Résistance d'isolement	≥500MΩ
Vie mécanique	≥3000次

Paramètres environnementaux

Classe de protection	MatchingIP67
----------------------	--------------

Accessoires

Caractéristiques commerciales

Numéro de la commande	25080000002
Unité d'emballage	
Quantité minimale de commande	
Le poid de produit (sans emballage)	