

Aperçu

informations sur le produit



ES-K-350-10090000081

Panel feed-through connectors for energy storage systems, rated current: 350A, rated voltage: 1000V, max cross section: 95mm², copper busbars: 20mm*5mm, color: orange, contact surface: Ni

Les avantages des produits

- ☒ The rotatable cover can effectively avoid the loss or damage of the cover at the construction site
- ☒ The pre cut structure can be flexibly removed according to the site conditions to enhance safety protection;
- ☒ The design of two-way opening can connect the energy storage battery in series or in parallel
- ☒ The product has low temperature rise to realize safe, economical and efficient connection

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Item properties

Type of installation	panel
Connection method	Screw connection
Number of potentials	1
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Nickel plating
Contact zone metal surface	Nickel plating

Insulation Materials	PC
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059
Environmental data	
Ambient temperature (operation)	-40°C~125°C

Accessoires

Caractéristiques commerciales

Numéro de la commande	10090000081
Unité d'emballage	16
Quantité minimale de commande	
Le poid de produit (sans emballage)	133.8