

Aperçu

informations sur le produit



DS4-HE-LD60-11040000191

Fuse terminal blocks, connector method: Push-in connector, Fuse type: G / 5 x 20, Glass/ceramic/..., Rated voltage : 60 V, Rated current : 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 6 mm², AWG: 24 - 10, Width: 6.2 mm, Color: black, Mounting type: NS35/7.5, NS35/15

Les avantages des produits

- ☑ Fuse terminal blocks.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Snap-on fuse box for easy fuse replacement.
- ☑ Equipped with LED indicator for quick identification of fusing status.
- ☑ Equipped with dual-channel bridge wells, circuit connection testing is more flexible.
- ☑ Equipped with test holes for easy testing of the circuit.

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Wiring data

Strip length	11~13mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	24~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
---------------------------------	---

Relative humidity (storage/transport)	25%~75%
---------------------------------------	---------

IEC Electrical parameters

Rated current (III / 3)	6.3A
-------------------------	------

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	55.6mm
width	6.2mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
fuse	G/5 x 20
Fuse type	Glass/ceramic/...

Accessoires

Marker

Top marker	ZB6 / ZS6
------------	-----------

Side marker	ZSF6
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	DFBXX-6.2
End cover	D-DS4-HE

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Caractéristiques commerciales

Numéro de la commande	11040000191
Unité d'emballage	100
Quantité minimale de commande	100
Le poid de produit (sans emballage)	9.705