

## Aperçu

### Informations sur le produit



## ESS-150A-35-B-OR-90-20160003062

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 35 mm², Rated voltage: 1500V, Rated current: 150 A, Connection method: Busbar, Contact type: needle

### Les avantages des produits

- ☒ Exclusive patents
- ☒ IP67 protection
- ☒ With safety locking latch
- ☒ The plug can rotate 360° after assembled
- ☒ The socket is with hand-proof protection
- ☒ With color-coded and mechanism-coded design avoiding misplug

### Les certificats des produits



## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

□

### Environment condition

|                                              |                |
|----------------------------------------------|----------------|
| Protection grade (pair plug)                 | IP67           |
| Ambient temperature (operation)              | -40°C ~ +125°C |
| Ambient temperature (storage/transportation) | -40°C ~ +80°C  |
| Altitude                                     | 2000m          |

### Wiring data

|             |        |
|-------------|--------|
| Wiring mode | Busbar |
|-------------|--------|

### Mechanical properties

|                 |        |
|-----------------|--------|
| Plugging times  | 100    |
| Pullout force   | >10N   |
| Insertion force | < 100N |

Standards and specifications

|                        |        |
|------------------------|--------|
| Standard/Specification | UL4128 |
|------------------------|--------|

Material data

|                                  |                           |
|----------------------------------|---------------------------|
| Insulating material              | Nylon                     |
| Halogen-free                     | Compliance with standards |
| Environmental protection matters | REACH/RoHS compliant      |
| Sealing ring material            | Silicone                  |
| Contact material                 | Copper alloy              |
| Shell color                      | Orange                    |
| Flammability rating              | UL94V-0                   |

Electrical parameters

|                       |            |
|-----------------------|------------|
| Pollution level       | 3          |
| Rated current         | 150A       |
|                       | UL DC1500V |
| Insulation resistance | >5000MΩ    |
| Contact resistance    | ≤0.5mΩ     |

Accessoires

Caractéristiques commerciales

|                       |             |
|-----------------------|-------------|
| Numéro de la commande | 20160003062 |
| Unité d'emballage     | 50          |

|                                     |    |
|-------------------------------------|----|
| Quantité minimale de commande       | 50 |
| Le poid de produit (sans emballage) | 46 |