

Aperçu

informations sur le produit

**DG2216R-15.0-10060007957**

PCB terminal blocks, Rated current: 76A, Rated voltage (III/2) : 600V, Cross section: 16mm², Pitch: 15.0mm, Connection method: Push-in spring connection, Color: Green, Contact surface: Tin

Les avantages des produits

- ☒ Push-in spring connection, excellent anti-vibration performance, tool-free.
- ☒ Dual-Lever Spring patented technology, easy and comfortable operation.
(Chinese patent for Utility Model,patent application number ZL201921625513.6)
- ☒ Levers status is optional (open/close), suitable for multi-core cable.

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D



Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section flexible

0.2~16mm²

Strip length

18mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

300V

Rated current (B)

66A

Rated current (C)	66A
-------------------	-----

Electrical parameters IEC

Rated voltage	600V
Rated current(III/3)	600V
Rated current	76A
Rated current(III/2)	600V
Rated current(II/2)	600V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	15mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessoires

Caractéristiques commerciales	
Numéro de la commande	10060007957
Unité d'emballage	70
Quantité minimale de commande	
Le poid de produit (sans emballage)	26.181