

Aperçu

informations sur le produit



9EDGRN-5.08-10020007144

Pluggable terminal blocks, Rated current: 16A. Rated voltage
(III/2) : 160V, pitch: 5.08mm, Color: green, Contact surface : Tin

Les avantages des produits

- ☒ PCB welding base
- ☒ Flexible supporting a variety of plugs

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Packaging information

Type of packaging

Plastic tray

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

14.5A

Rated current (D)

10A

Electrical parameters IEC

Rated voltage	160V
Rated current(III/3)	160V
Rated current	16A
Rated current(III/2)	160V
Rated current(II/2)	320V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	5
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PBT
Relative tracking index CTI	400V
Glow Wire Flammability Index GWFI	850
Shell color	Black
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-30°C~120°C

Accessoires	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

Caractéristiques commerciales	
Numéro de la commande	10020007144
Unité d'emballage	290
Quantité minimale de commande	290
Le poid de produit (sans emballage)	6